

CTP-TLF14NHV

4 MP H.265 NETWORK IR OUTDOOR DOME CAMERA

IP
CAMERA





FUNCTION

- H.265 Main Profile Video Compression Technology
- 4MP (2592 × 1520) H.265 Full Real Time Coding
- Max. Resolution: 2592 × 1520
- ICR Auto Switch, True Day & Night
- Up to 60ft. IR Night View Distance
- 3D DNR, True WDR
- ROI Coding
- Support Local CVBS Video Output and One-way Audio
- Support Hardware Reset
- Support PoE Power Supply
- Support Smartphone, iPad, Remote Monitoring Support P2P
- IP66 & IK10 Ingress Protection
- Support Three Streams



DIMENSION

* Unit : mm (Inch)




SPECIFICATION

DESCRIPTION	CTP-TLF14NHV
Image Sensor	1/3" CMOS
Effective Pixels	2592 x 1520
Electronic Shutter	1/25s ~ 1/100000s
Min. Illumination	Color: 0.05lux@F1.2, AGC ON, B/W: 0lux with IR
Lens	3.6mm MP Fixed Lens
Lens Angle	Horizontal: 72°
Lens Mount	M12 Mount
WDR	True WDR
BLC	Yes
DNR	2D / 3D DNR
Video Compression	H.265 MP, H.264 BL / MP / HP, MJPEG
Audio Compression	G.711A / G.711U
Bit Rate	64Kbps ~ 10Mbps
Encode Mode	VBR / CBR
Image Quality	Five Levels under VBR; Freely Adjustable under CBR
Resolution	4MP (2592 x 1520), 3MP (2304 x 1296), 1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Multi-Stream	4MP (1~30fps) / 3MP (1~30fps) / 1920 x 1080 (1~30fps) / 720P (1~30fps) / 720P (1~30fps) / D1 (1~30fps) / CIF (1~30fps) / D1 (1~30fps) / 480 x 240 (1~30fps) / CIF (1~30fps)
Image Setting	ROI, Saturation, Brightness, Hue, Contrast, WDR, Sharpness, DNR, etc.
Network	RJ45
Video Output	CVBS (BNC x 1)
Audio	One-way Audio (MIC In x 1)
Card Storage	No
RS485	No
Alarm Input	No
Alarm Output	No
Remote Monitoring	Browser, CVMS, Mobile CVMS
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	Max. 10 Online Users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA / OSC / AVD
Day & Night	True
IR Distance	60ft.*
IR LED (Count)	24 (Φ4 12mil)
Weatherproof	IP66
Angle Adjustment	Horizontal: 0° ~ 68°, Vertical: 0° ~ 220°, Rotation: 0° ~ 240°
Power Supply	DC 12V/PoE
Power Consumption (IR Off)	<2.5W
Power Consumption (IR On)	<4W
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C), 10% ~ 90% Relative Humidity
Dimension	Φ4.6" x 3.6" (Φ116mm x 91mm)
Weight	605g

*IR distance range varies depending on the environment

FEATURE



Our IP cameras offer a complete set of input and output connectors for easy installation.

- Built-in PoE (Power over Ethernet) Port
- DC 12V Power
- CVBS Analog BNC Out
- Audio In (MIC)