





ED3A-8

8 Ch TVI/AHD/CVI/Analog/IP Universal Port Recorder (5 MP), with 8 Bonus IP Ch (5/8 MP), Up to 16 cameras total, 2 HD Bay, 4K

Features

- 8 Channel Universal Port DVR (TVI/AHD/CVI/IP/Analog/IP)
- Up to 5MP Support on HD Analog Channels
- 8 Bonus IP Channels
 Up to 5 Megapixel in Hybrid IP Mode*
 Up to 8 Megapixel in Full IP Mode**
- Total Max IP Input: 16 (Including Bonus IPC)
- H.265/H.265+/H.264/H.264+ Video Compression
- True P2P Connectivity with QR Code Connect
- Simultaneous HDMI/VGA up to 1080p Resolution
- CVBS Main or Spot Monitor
- HDMI up to 4K Resolution
- Supports up to 8 Channel Simultaneous Playback
- Multiple video search options including Smart and Thumbnail Search for quick retrieval of footage.
- Store and access video storage to the Cloud
- Upgrade your recorder via the Cloud
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Mode Chart

Model Name	Max Megapixel for IPC	
	Hybrid Mode	Full IP Mode
ED3A-4, ED3A-8, ED3A-16	5 MP	8 MP

*Hybrid Mode: Analog camera and IP camera can be added at the same time.
**Full IP Mode: Convert all channel type to IP, only IP camera can be added

Ordering Information **ED3A-8:** 8 Ch Universal Port Recorder

Available with 2/4/8/10/16/20 TB Hard Drive Options

Model	ED3A 8
Model Chinsot	ED3A-8
Chipset Video & Audio Input	Hi3531D
	9ah(10)(a p. 75 0)
Analog Video Input HDTVI Input	8ch(1.0Vp-p, 75 Ω) 8MP,5MP,4MP,1080P, 720P
·	
CVI Input	8MP,4MP,1080P, 720P
AHD Input	8MP,5MP,4MP,1080P, 720P
CVBS Input	Support
P video Input	Support 1/O
Audio Input	4-ch, RCA(2.0 Vp-p, 1 KΩ)
Two-Way Audio	1-ch, multiplex with Audio Input(RCA)
Video & Audio Output	4//39 40 - 2140 /30 In 1000 - 1000 /40 In 1000 - 1004 /40 In 1000 - 720 /40 In 1
HDMI	4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1 024×768/60Hz
VGA	1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
CVBS	BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
Audio Output	1-ch, RCA(Linear, 1kΩ)
Recording	I-CII, NCA(Linear, 1822)
	H.265+/H.265/H.264+/H.264
Video Compression	8MP/5MP/4MP/1080P/1080P Lite/720P/960H/D1
Encoding Resolution	
Resolution	Main stream:8MP@7fps, 8MP-N@15fps, 5MP@12fps,4MP@15f- ps,1080P/720P/960H/D1@25fps(P)/30fps(N)
Frame Rate(fps)	1-25fps
Video Bit Rate	11Kbps~ 10Mbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Compression Audio Bit Rate	6.711d 64kbps
Bonus IPC Input	U4KDP3
Hybrid Resolution	5MP/4MP/3MP/2MP/720p/960H
Full Resolution	8MP/5MP/4MP/3MP/2MP/720p/960H
Hybrid Frame Rate	5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
Full Frame Rate	8MP/5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
IP Input	5 AD / 4 AD / 2 AD / 2 AD / 2 AD / 7 CO ~ / C / C L
Hybrid Resolution	5MP/4MP/3MP/2MP/720p/960H
Full Resolution	8MP/5MP/4MP/3MP/2MP/720p/960H
Hybrid Frame Rate	5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
Full Frame Rate	8MP/5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
IPc Input/Access Band- width	IPC x 8 / 120Mbps (Hybrid), IPC x 16 / 160Mbps (Full)
Total Max IP Input	16 (including Bonus IPC)
•	10 (Including bonus Irc)
Playback & Backup	ACLURAD Diguidados OCUENAD NEDIguidados
Playback Number	4CH 8MP Playback, 8CH 8MP-N Playback
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture playback
Backup Mode	USB Device/Network/External HDD
Advanced Features	
Smart Detection for	8 line crossing detection,intrusion detection
Analog Video Quality Detection	8CH Defocus Detection
Smart Detection for IPC	Line crossing detection, Area Intrusion detection, Region Entrance, Re- gion Exiting, Fast moving, Unattached Object, Object Missing, Face
	Detection
Smart Playback for Analog	Line Crossing/Are Intrution/Motion Detection
Smart Playback for IPC	Face detection/Line Crossing/Are Intrution/Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-
	cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P
Web Client	User Defined, Max 32 Users
Hard Disk	
SATA	2 SATA interfaces
Capacity	Up to 10TB capacity for each HDD (Western Digital Only for 10TB
<u> </u>	Drives)
External Interface	
Serial Interface	1*Standard RS-485(half-duplex)
USB Interface	"Front panel: 1 × USB 2.0;
	Rear panel: 1 × USB 2.0"
Alarm Input	4ch
Alarm Output	1ch
General	
Power Supply	DC12V,5A
i Owci Jappiy	<20/4/(ithot.I.IDD)
	≤20W(without HDD)
Power Consumption	-10°C~+55°C / 10%~90%RH
Power Supply Power Consumption Working Environment Dimension (W×D×H)	