



POH1000 & POH1500

Outdoor Environmental Housing

- Side hinges for ease of access when focusing and adjusting the camera
- Easy camera installation
- Accepts many lens and camera combinations
- Optional 24VAC heater/blower (H&B), sunshield
- Built-in thermostatically controlled 24VAC H&B on POH1000HB and POH1500HB models
- Lightweight aluminum chassis
- POH1000/POH1000HB models: Fits all current Panasonic 1/3" cameras with all Panasonic fixed focal length 1/2" and 1/3" ALC lenses
- POH1500/POH1500HB models: Longer version, fits all current Panasonic cameras with all Panasonic fixed focal length and zoom lenses



Bid Specifications

POH1000 / POH1000HB:

The indoor/outdoor extruded aluminum camera housing shall be a Panasonic Model POH1000/POH1000HB or equivalent. The housing shall be compatible for use with a 1/3" Panasonic CCD camera with Panasonic fixed focal or varifocal (manual zoom) lens. The housing shall include a side hinge for ease of access for focus adjusting and servicing. The housing shall be suitable for use with a sun shield (PSS10). The housing shall be compatible for use with the following mounts: WV-831P light duty mount; PWM800 medium duty wall/pole mount; and PCM800 medium duty corner mount. The housing's dimensions shall not exceed (HxWxL) 4.42" x 5.67" x 13.25" (112.3 x 144 x 336.6mm). The housing's weight shall not exceed 4 Lbs. The power source shall be 24VAC, 60Hz. The POH1000 housing shall be compatible for use with a heater or blower. POH1000HB housing shall include a factory-installed H&B.

POH1500 / POH1500HB:

The indoor/outdoor extruded aluminum camera housing shall be a Panasonic Model POH1500/POH1500HB or equivalent. The housing shall be compatible for use with a 1/2" or 1/3" Panasonic CCD camera with Panasonic zoom lens. The housing shall include a side hinge for ease of access for focus adjusting and servicing. The housing shall be suitable for use with a sun shield (PSS15). The housing shall be compatible for use with the following mounts: WV-831P light duty mount; PWM800 medium duty wall/pole mount; and PCM800 medium duty corner mount. The housing's dimensions shall not exceed (HxWxL) 4.42" x 5.67" x 18.25" (112.3 x 144 x 463.6mm). The housing's weight shall not exceed 4 Lbs. The power source shall be 24VAC, 60Hz. The POH1500 housing shall be compatible for use with a heater or blower. POH1500HB housing shall include a factory-installed H&B.

Specifications

ELECTRICAL SPECIFICATIONS		
Power Requirements		
POH1000 / POH1500	24VAC, 60Hz	
POH1000HB / POH1500HB	24VAC, 60Hz, 27 watts (excluding camera)	
Heater	24VAC, 60Hz, 25 watts	
Blower	24VAC, 60Hz, 1.4 watts	
MECHANICAL SPECIFICATIONS		
Size (HxWxD)		
POH1000 / POH1000HB	4.42" x 5.67" x 13.25" (112.3 x 144 x 336.6mm)	
POH1500 / POH1500HB	4.42" x 5.67" x 18.25" (112.3 x 144 x 463.6mm)	
Weight	3.9 Lbs. (2 Kg) (without camera)	
Construction		
Housing body	Extruded aluminum, powdercoat beige finish	
Endcaps	Black polycarbonate	
ENVIRONMENTAL SPECIFICATIONS		
Operating Temperature	-20°F to 120°F (-29°C to 49°C)	
Heater activates at	60°F (+/- 8°F)	
Heater deactivates at	80°F (+/- 5°F)	
Blower activates at	110°F (+/- 7°C)	
Blower deactivates at	80°F (+/- 6°F), 24VAC, 1.4W	
SHIPPING SPECIFICATIONS	WEIGHTS	DIMENSIONS
POH1000 / POH1000HB	5 Lbs. (2.3 Kg)	5" x 6" x 16" (127 x 152.4 x 406.4mm)
POH1500 / POH1500HB	6 Lbs. (3 Kg)	5" x 6" x 20" (127 x 152.4 x 508mm)



Certifications/Ratings



<http://panasonic.com/security>

Panasonic System Networks Company of America

Surveillance, Monitoring and Video Imaging

Panasonic Service Center
415 Horizon Drive
Suite 350-B
Suwanee, GA 30024
(770) 904-8350

Design and specifications subject
to change without notice.

03172011