

Intensifier3® Series Indoor/Outdoor Dome/Turret Camera


See Color In Almost Complete Darkness Without IR LEDs

- HTINTD8** 2.8 - 12mm auto iris varifocal lens, dark grey housing
- HTINTD8W** 2.8 - 12mm auto iris varifocal lens, white housing
- HTINTD9** 5 - 50mm auto iris varifocal lens, dark grey housing
- HTINTD9W** 5 - 50mm auto iris varifocal lens, white housing
- HTINTD10** 9 - 22mm auto iris varifocal lens, dark grey housing
- HTINTD10W** 9 - 22mm auto iris varifocal lens, white housing

Features

- 1/3" Sony Super HAD II™ CCD
- 650 TV lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier3® @ 512x)
- 12VDC / 24VAC dual voltage operation
- Full OSD operation and test monitor output
- Now with Presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- 3-axis wall or ceiling mount
- External controls for zoom & focus
- EZ mount system simplifies installation
- Relay outputs for motion detection
- Weather resistant operation
- IP66 compliant
- Anti-moisture glass and circuitry eliminates fog or condensation under any weather condition
- 5 year warranty

**INT
3**



Specifications

Image Sensor	1/3" Sony Super HAD II™ CCD	White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,700°K – 11,000°K)
Resolution.....	650 TV lines	Intensifier3®	Auto / Off (selectable 2x – 512x)
Minimum Illumination.....	0.00002 lux	Motion Detection.....	On / Off (8 programmable zones)
Total Pixels	811 (H) x 508 (V)	Privacy Masking	On / Off (12 programmable zones)
Effective Pixels	768 (H) x 494 (V)	Speco DNR.....	On / Off (level adjustable)
TV System.....	NTSC	Digital Zoom	On / Off (1x - 16x)
Scanning Frequency.....	15.734kHz (H) / 59.94Hz (V)	DIS.....	On / Off
Scanning System.....	2:1 interlace	Sharpness	On / Off (level adjustable)
Synchronization	Internal	Flip / Mirror	On / Off
S/N Ratio	More than 52dB	Power Consumption	12VDC, 400mA / 24VAC, 170mA
Video Output.....	CVBS: 1.0Vp-p / 75 ohms	Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Electronic Shutter Speed.....	1/60 sec. - 1/120,000 sec.	Operating Temperature.....	- 4° F – 140° F
OSD.....	Available	Dimensions	4.36" (H) x 5.47" (Dia.)
WDR.....	On / Off (level adjustable)	Weight	3.08 lbs.
Backlight Compensation.....	BLC / HLC / Off		
Day/Night.....	Color / BW / Auto		
AGC.....	High / Low / Off		

Optional Accessories



INTPM
Pendant
Mount



JB03TG
Large Round
Junction Box



INTWM
Wall Mount



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/21/14