

Intensifier® 3 Series Indoor/Outdoor Turret Camera


See Color In Almost Complete Darkness Without IR LEDs

HTINTD8W	2.8-12mm auto iris varifocal lens, white housing
HTINTD9W	5-50mm auto iris varifocal lens, white housing
HTINTD10	9-22mm auto iris varifocal lens, dark grey housing
HTINTD10W	9-22mm auto iris varifocal lens, white housing

Features

- 1/3" Sony Super HAD II™ CCD
- 650 TV lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier® 3 @ 512x)
- 12VDC / 24VAC dual voltage operation
- Full OSD operation and test monitor output
- Presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- 3-axis wall or ceiling mount
- External controls for zoom & focus
- EZ mount system simplifies installation
- Relay outputs for motion detection
- Weather resistant operation
- IP66 compliant
- Anti-moisture glass and circuitry eliminates fog or condensation under any weather condition
- 5 year warranty

**INT
3**



Specifications

Image Sensor	1/3" Sony Super HAD II™ CCD
Resolution.....	650 TV lines
Minimum Illumination.....	0.00002 lux
Total Pixels	811 (H) x 508 (V)
Effective Pixels	768 (H) x 494 (V)
TV System.....	NTSC
Scanning Frequency.....	15.734kHz (H) / 59.94Hz (V)
Scanning System.....	2:1 interlace
Synchronization.....	Internal
S/N Ratio	More than 52dB
Video Output.....	CVBS: 1.0Vp-p / 75 ohms
Electronic Shutter Speed.....	1/60 sec. - 1/120,000 sec.
OSD.....	Available
WDR.....	On / Off (level adjustable)
Backlight Compensation.....	BLC / HLC / Off
Day/Night.....	Color / BW / Auto
AGC.....	High / Low / Off

White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,700°K – 11,000°K)
Intensifier3®	Auto / Off (selectable 2x – 512x)
Motion Detection.....	On / Off (8 programmable zones)
Privacy Masking	On / Off (12 programmable zones)
Speco DNR.....	On / Off (level adjustable)
Digital Zoom	On / Off (1x - 16x)
DIS.....	On / Off
Sharpness	On / Off (level adjustable)
Flip / Mirror	On / Off
Power Consumption	12VDC, 400mA / 24VAC, 170mA
Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Operating Temperature.....	- 4° F – 140° F
Dimensions	4.36" (H) x 5.47" (Dia.)
Weight	3.08 lbs.

Optional Accessories



INTPM
Pendant
Mount



JB03TG
Large Round
Junction Box



INTWM
Wall Mount



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply