



PAR-C5TXIRA2812

5 Megapixel, TVI/AHD/CVI/CVBS Outdoor Turret, 2.8-12mm Motorized A/F, 98' IR Range, 12VDC

Features

- 5 Megapixel Resolution (2592 x 1944)
- Motorized Auto-Focus 2.8-12mm Lens
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- 98' Smart IR Range
- True Day/Night
- D-WDR
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client

Camera	PAR-C5TXIRA2812
Image Sensor	1 / 2.7 " CMOS
Resolution	5MP/4MP
Image Size	2592 x 1944
Video Output	AHD / TVI / CVI / CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 50s ~ 1 / 100000s (PAL); 1 / 60s ~ 1 / 100000s (NTSC)
IR Distance	98 ft.
Frame Rate	5MP @20fps, 4MP @30FPS
Min. Illumination	Color : 0.01 lux@F1.2, AGC ON; B/W : 0 lux with IR
Lens	2.8-12 mm, Automatic Focusing And Motorized Zoom Lens
Lens FOV	2.8-12mm: 91.2°-33.4° H, 75°-25.4° V, 108°-41.2° Crossline
Lens Mount	D14
S/N Ration	≥52dB (AGC OFF)
Ingress Protection	IP66
Functions	
Function Control	OSD (UTC Control)
Day & Night	ICR
Digital WDR	Yes
Digital NR	Yes
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front light compensation	Yes
HLC	Yes
Sharpness	Yes
Mirror Image	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto / Manual
Language	13 languages
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°
Others	
Power Supply	DC12V (± 10%)
Power Consumption	IR OFF : < 1W; IR ON : < 3W
Working Environment	-22°F ~ 122°F(-30 °C ~ 50 °C), 10% ~ 90% (relative humidity)
Dimensions	5.1 x 4.2 in (130.3 x 109mm)
Weight	Approx. 1.4 lbs (0.66KG)

Ordering Information

PAR-C5TXIRA2812: 5 Megapixel Turret, 2.8-12mm