



New York Branch
 217 Knickerbocker Ave
 Bohemia, NY 11716
 Tel: 631-392-1701
 Fax: 631-392-1702
 www.sdicable.com

CA Branch
 4225 Remington Ave
 Temecula, CA 92590
 Tel: 951-394-8694
 Fax: 631-392-1702

Alarm Cable Unshielded Specification Sheet

Product Construction

Conductor:
 Annealed Solid or stranded bare copper

Insulation:
 PVC
 Color code: see chart below

Jacket:
 PVC (color optional)
 Suitable for use from -20°C to +75°C
 Every 2 feet sequential marking
 Include ripcord

Applications:
 Power-limited control circuits
 Wiring of following systems:
 Intercom
 Security
 Audio
 Background music
 Suggested voltage rating: 300V

Compliances:
 UL Type CMR

Color Code Chart

No. of Cond.	Color
1	Black
2	Red
3	White
4	Green

Part No.	Description	NO.of Cond.	AWG Size	Solid/Stranded	Nom. Insulation Dia.m	Nom. Jacket Dia. Mm
AW22-2SLCU	Alarm Wire 22/2 Solid 1000ft UL CMR White	2	22	Solid	1.04	3
AW22-4STCU	Alarm Wire 22/4 Stranded 1000ft UL CMR White	4	22	stranded	1.04	3.2
AW22-4SLCU	Alarm Wire 22/4 Solid 1000ft UL CMR White	4	22	Solid	1.04	3.2
AW18-2STCU	Alarm Wire 18/2 Stranded 1000ft UL CMR White	2	18	stranded	1.42	3.96
AW18-4STCU	Alarm Wire 18/4 Stranded 1000ft UL CMR White	4	18	stranded	1.42	4.75

Cable printing:
 Alarm Cable Part No. *AWG/*C (UL) E362025 CMR SUN RES (quality tracking NO) 002FT—****FT
 for example of AW22-2SLCU
 Alarm Cable AW22-2SLCU 22AWG/2C (UL) E362025 CMR SUN RES (quality tracking NO) 002FT—****FT

Package:
 easy pull box