

## DS-1H05 Series

## **Coaxial Transmission Device**

- Transmits Analog/IP Signal Over Coaxial Cable
- .310 Miles (500 M) Maximum Transmission Distance
- Use as Range Extender for Analog
- Industrial Design, High Reliability

Hikvision's DS-1H05 Series Coaxial Transmission Device provides a security link using coax technology, to transmit analog and IP signals over coaxial cable.



DS-1H05-T



DS-1H05-R

## **Available Models:**

DS-1H05-T: One channel transmitter DS-1H05-R: One channel receiver

DS-1H05-T	DS-1H05-R	
1 RJ-45,1 BNC	1 BNC	
1 BNC	1 RJ-45, 1 BNC	
Single-channel transmitter	Single-channel receiver	
Digital or Analog (CVBS)	Digital or Analog (CVBS)	
N/A	3 to 11 Mbps	
21 to 36 Mbps		
.310 miles (500 meters)		
≤5 W	≤5 W	
10	% to 90%	
50° F to 131° F (-10° C to 55° C)		
12 VDC (included)		
3.15" x 1.06" x 3.78"	3.15" x 1.06" x 3.78" (80 mm × 27 mm × 96 mm)	
	1 BNC Single-channel transmitter Digital or Analog (CVBS) N/A 21 to 36 Mbps .310 mile ≤5 W 10 50° F to 131' 12 VE	



<sup>&</sup>lt;sup>1</sup> Higher bandwidth speed results in shorter transmission distance

<sup>&</sup>lt;sup>2</sup> Transmission distance is affected by the type of coaxial cable used