

ACTUATOR RELAY

Intelligent Simplebus device for controlling a 10 A (12-24 V relay contact) on board. It can be used in Simplebus 1 and Simplebus 2 systems. Depending on the position of the jumper, the device provides six distinct functions: call repetition, activation on porter switchboard call pushbutton, door opening (without external unit), activation on actuator pushbutton, activation on actuator pushbutton with code. For use and programming of the function required, follow the indications given in the technical documentation. If used in mixed audio/video systems, the actuator relay needs terminal art. 1214/2 to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 2.6?x3.3?x1.4?. (4 DIN modules).



Compatibility

Simplebus Top system:	Yes
Simplebus Color system:	Yes
Simplebus 2 system:	Yes

Mounting/Installation

Wall-mounted:	No
DIN rail mounted:	Yes
DIN modules (no.):	4

Audio/video specifications

Audio system:	Yes
Audio/video system:	Yes

Technical properties

Temperature range (°C):	0 / 40
-------------------------	--------

Electrical specifications

Maximum current absorption (mA):	50
----------------------------------	----

General info

EAN product code:	'8023903131499
Intrastat code:	85176920
Product height (mm):	85
Product width (mm):	66
Product depth (mm):	35

Packaging

Single pack height (mm):	53
--------------------------	----

DATA SHEET

Single pack width (mm):	110
Single pack weight (g):	200
Single pack depth (mm):	94
Single pack volume (dm3):	0,548