

KBDPTZ1

Features

- Capable of controlling up to 32 speed domes
- 2 levels of passwords (administrator and user) are supported for higher security
- Programmed data from up to 2 domes can be downloaded to non-volatile memory space and uploaded to a new dome
- Control a camera's panning and tilting movement with variable speeds from 0.5'/sec. to 90'/sec., as well as its zoom, focus and iris command
- Normal speed is inversely proportional to the current zoom ratio
- Turbo speed is max. 380'/sec. when "Ctrl" key is pressed
- Define and recall up to 240 presets, which are immediate camera call-ups of preset position view with automatic zoom and focus
- Able to define and run up to 8 patterns comprising of a sequential series of pan, tilt, zoom and focus movements from a single camera
- Define and run up to 8 scans which scan between 2 limits
- Incorporate up to 300 presets, patterns, scans and 8 tours
- Presets, patterns and scan are automatically displayed one after the other on the main monitor
- Programmable user preferences (alarm, preset, title, etc.)



Specifications

Power Consumption12VDC, 0.5W
 Control Method.....RS-485
 Baud Rates.....RS-485 2400 - 230K bps
 Dimensions.....15" (W) x 6.5" (L) x 2.75" (H)
 Weight2.5 lbs.
 Power Supply12VDC@1.5A
 (power supply included)

Controls the Following Dome Cameras:

HTSD10X	HT65010XS	OPTZ36XO
HTSD37X	HT650PT10X	OPTZ36XI

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/28/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com