

RLK16-800B8-NVR-Kit-NVR-Specifications		
	Model	RLN16-410
Hardware	Hardware	V2
Video/Audio Input	IP Video Input	PoE IP Camera x 16
	Audio Input	Cameras with Built-in Mic
Video/Audio Output	HDMI Output	3840x2160, 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768
	VGA Output	1920x1080, 1280x1024, 1280x720, 1024x768
	Audio output	1CH RCA
Decoding	Live View/Playback Resolution	3840x2160, 2560x1920, 2560x1440, 2048x1536, 2304x1296, 1080p, 720p
	Video Format	H.264
	Synchronous Playback	Up to 4 Channels
Storage	SATA Devices	2 SATA Interfaces for HDD (3TB Included)
	Maximum Capacity	Up to 4TB for Each HDD
	External HDD	No
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1 x RJ45 10/1000 Mbps Self-Adaptive Ethernet Interface for LAN/WAN
		16 x RJ45 10/100 Mbps Self-Adaptive PoE Ethernet Interface for IP camera
PoE	Max. Power Consumption/Port	25W
	Supported Standard	IEEE 802.3 af/at
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browser Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	DC 48V/2.5A
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10℃~+55℃ (14°F~131°F); Humidity: 10%~90%
	Dimensions (mm)	330(W) x 45(H) x 285(D)
	Weight (With HDD)	2.4 kg
Warranty	Limited Warranty	2-Year Limited Warranty. For Support, Visit https://support.reolink.com/hc/en-us/