

Overview

Control Concord panels with either the ATP-1000 Alphanumeric programmable touchpad or the FTP-1000 Fixed English touchpad. Messages are displayed in a large and easy-to-see LCD window, and emergency keys are highlighted on the touchpad for safety.

Both the ATP-1000 and the FTP-1000 touchpads allow control of Concord Express, Concord 3, Concord Ultra, and Concord 4 products. The large display provides easy-to-read messages that indicate the current status of the system. In addition, the ATP-1000 touchpad can be used for installer/user programming of the Concord control panels and has the added capability of displaying customized zone naming text.

Both touchpads include police, fire, and auxiliary panic buttons that can be activated any time. A built-in speaker provides alarm, status, and buttonpress sounds. The swing-down door reveals a label with basic system operating commands—or remove the door by simply opening it past its stop point. The door can be reattached later if desired. Emergency keys are highlighted on the keypad for safety and ease of use. All keys are backlit to insure error free operation—even in a dark room.

Standard Features

- Large easy-to-read display
- Improved backlighting of display and keys for better visibility
- Stand-alone panic keys
- Stand-alone arming keys
- Traditional design to blend with any décor
- Easy to install

ATP-1000 and FTP-1000

Touchpads for use
with Concord™ Systems



ATP-1000

FTP-1000



North America
T 888-437-3287

Asia
T 852-2907-8108
F 852-2142-5063

Australia
T 61-3-9239-1200
F 61-3-9239-1299

Europe
T 32-2-725-11-20
F 32-2-721-40-47

Latin America
T 561-998-6100
F 561-994-6572

interlogix.com
utcfireandsecurity.com

Specifications subject to change without notice.

© 2010 Interlogix, A UTC Fire & Security Company.
All rights reserved.



is a trademark of General Electric
Company and is used under license to
UTC Fire & Security, 9 Farm Springs Road,
Farmington, CT 06034-4065

Specifications

Compatibility	Concord 3, Concord Express, Concord Ultra, Concord 4
Electrical	Voltage: 12 VDC nominal Current: 75 mA (FTP-1000) Current: 60mA typical, 110mA in alarm (ATP-1000)
Environmental	Operating temperature: 32 to 120°F (0 to 49°C) Storage temperature: -30 to 140°F (-34 to 60°C) Relative humidity: 85% max., noncondensing
Physical	Dimensions (LxWxD): 5.0 x 4.50 x 0.75 in. (127 x 114 x 19 mm)
Regulatory	UL/cUL listings: UL (985, 1023, 1610) cUL (C1023 - 1974, S545 - M89)

For cUL listed applications, the unit shall be installed in accordance with Part 1 of the Canadian Electrical Code.

Ordering Information

600-1020	Fixed English touchpad
60-983	Alphanumeric touchpad