

Q950

6MP Door Station Outdoor Door Station with D/N, IR, Extreme WDR, SLLS, Fixed Lens



- Door Station
- 6 Megapixel
- Day & Night with Superior Low Light Sensitivity and IR LED
- Fixed Lens with f1.65mm/F2.8
- Extreme WDR
- Super wide angle
- Event trigger, response and notification

► Specifications

Device

| | |
|--------------------------|--|
| Product Type | Door Station |
| Maximum Resolution | 6MP |
| Product Application | Door Station |
| Application Environment | Outdoor |
| Description | 6MP Outdoor Door Station with D/N, IR, Extreme WDR, SLLS, Fixed lens (f1.65mm) |
| Image Sensor | Progressive Scan CMOS |
| Sensor Size | 1/1.8 " |
| Effective Pixels | 3096(H) X 2080(V) (6.44 MP) |
| Day / Night | Yes |
| Low Light Sensitivity | Superior |
| Minimum Illumination | Color: 0.1 lux at F2.8 (30 IRE, 2400 K); B/W: 0 lux at F2.8 (IR LED on) |
| Color to B/W Switch | ISP based switch, configurable |
| Mechanical IR Cut Filter | Yes |
| IR Sensitivity Range | 700-1100nm |
| IR LED | IR LED x 6 (850 nm) |
| IR Working Distance | 5m |

| | |
|----------------------------------|--|
| Electronic Shutter | 1/5-1/64000 second (manual mode); 1/5-1/64000 second (auto mode) |
| Horizontal Resolution (TV Lines) | 1800 TVL |
| S/N Ratio | 56 dB |

Lens

| | |
|--------------------------|--|
| Focal Length | Fixed focal, f1.65mm |
| Aperture | F2.8 |
| Iris | Fixed iris |
| Focus | Fixed focus |
| Lens Mount | Board mount |
| Horizontal Viewing Angle | 198.5° (overview area) 121.1° (high detail area) |
| Vertical Viewing Angle | 198.5° (Fisheye View) |

Video

| | |
|-----------------------------------|---|
| Compression | H.264 (Baseline/ Main/ High profile), MJPEG |
| Maximum Frame Rate vs. Resolution | (Fisheye View) 20 fps at 3072 x 2048 30 fps at 2048 x 2048 20 fps at 1280 x 960 30 fps at 1024 x 768 30 fps at 800 x 600 30 fps at 640 x 480 (Dewarped View) 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 640 x 480 |
| View Mode | Fisheye View Dewarped View |
| Multi-Streaming | Simultaneous triple streams based on three configurations |
| Bit Rate | 128Kbps - 12Mbps (per stream) |
| Bit Rate Mode | Constant, Variable |
| Wide Dynamic Range | Extreme WDR (130 dB) |
| Image Enhancement | White Balance, Brightness, Contrast, Sharpness, Automatic gain control, Flickerless, Defogging |
| Digital Noise Reduction | 2D + 3D DNR |
| Privacy Mask | 4 configurable regions |
| Text Overlay | Yes |
| Built-in Analytics | Tampering Detection*, Shock Detection, RFID Recognition |
| Server-based Analytics | Object Line Counting, People Counting, Face Detection, Object Based Motion Detection, Tamper, Object Line Crossing Detection, Object Enter Area Detection, Missing Object Detection, Unattended Object Detection, Smoke Detection, Heat Map, Dwell Time, Direction Detection, Automatic License Plate Recognition, People Queue Detection, (Require PC-based or standalone IVS or ALPR Server. Contact ACTi support for recommendations on how to maximize analytical accuracy) |

Audio

| | |
|-------------------|--|
| Audio Type | 2-way, Built-in Microphone, Built-in Speaker, Line-out |
| Audio Compression | 8 kHz, 16 bit encoding, Mono, PCM, G.711 |

Network

| | |
|----------------------------|---|
| Network Protocol & Service | IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, IGMP, ICMP, ARP, Bonjour, UPnP, QoS, SNMP, IEEE 802.1X |
| Ethernet Port | 1 x RJ-45 connector |
| Security | IP address filtering, HTTPS encryption, Password protected user level, Anonymous login, IEEE 802.1X network access control |

Video Analytics

| | |
|----------------------|----------|
| Analysis Source Type | Video |
| Metadata Accuracy | Standard |

Event

| | |
|----------------|--|
| Event Trigger | Passive IR sensor, Touch button, RFID detection, External device through digital input, Sound detection, Tampering detection*, Shock Detection |
| Event Response | Notify control center, Change camera settings, Command other devices, E-mail notification with snapshots, Play the audio file, Push notification to mobile device, Save video to local storage, Upload video to NVR server, Upload video or snapshot to FTP server, Activate external device through digital output, Change LED indicators |

Access Control Functionality

| | |
|-------------|-----------|
| Access Mode | Card only |
|-------------|-----------|

RFID Card

| | |
|-------------------------|--|
| Communication Frequency | 13.56 MHz |
| RFID Standard | NFC Type 1, ISO/IEC 14443A NFC Type 2, ISO/IEC 14443A NFC Type 3, ISO/IEC 18092 NFC Type 4, ISO/IEC 14443 (Type A/B) NFC Type 5, ISO/IEC 15693 |
| RFID Options | NFC |

Integration

| | |
|-----------------------|--|
| Unified Solution | Fully compatible with ACTi software |
| GPS Position | Manual setting |
| ONVIF Compliant | Yes, Profile S, Profile G, Profile T* (To be available through future firmware upgrade), Profile Q |
| Web Browser | IE 11 |
| Auto Firmware Upgrade | Yes* (To be available through future firmware upgrade) |

Interface


| | |
|----------------------|---|
| Serial Port | 1 x RS-485/RS-422 |
| Audio Interface | Terminal block |
| Local Storage | MicroSDHC, MicroSDXC memory card slot (card not included) |
| Digital Input/Output | 1/1 |

General

| | |
|-----------------------|--|
| Power Source | DC 12V, PoE Class 3 (IEEE802.3af) |
| Power Consumption | 4.2 W (PoE), 3.8 W (DC) |
| Weight | 689g (1.52lb) |
| Dimensions | (W x H x D): 177.06mm x 110mm x 47.66mm (7.0" x 4.3" x 1.9") |
| Environmental Casing | Weatherproof (IP66), Vandal resistant (IK09) |
| Mount Type | Surface, Gang Box |
| Starting Temperature | -40°C ~ 50°C (-40°F ~ 122°F) |
| Operating Temperature | -40°C ~ 50°C (-40°F ~ 122°F) |
| Approvals | CE, FCC, IP66, IK09, NEMA 4X, UL (for optional PoE injector and power adapter) |
| Warranty | 3 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty |


* To be available through future firmware upgrade

► Photo Indication



- 1 Passive IR sensor
- 2 IR LEDs
- 3 Fisheye Lens
- 4 Built-in Speaker
- 5 Push Button
- 6 RFID Reader
- 7 Built-in Microphone
- 8 Power LED
- 9 Reset Button
- 10 Memory Card
- 11 Audio Output Switch
- 12 Audio Output
- 13 Serial Port Connector
- 14 Digital Input/Output
- 15 Network Connector
- 16 Power Input



► Dimension Diagram




Unit: mm [inch]

▶ Related Products






Access Control System - Access Control Server

| | | |
|---------|---|--|
| ACS-100 |  | 200-Channel 1-Bay Mini Standalone Access Control Server with HDMI, DVI and Display port, 4-channel free license included, Supports External Storage (eSATA, iSCSi), 1-Bay (Storage Disks not included), Audio, AC 100-240V |
| ACS-400 |  | 400-Channel 1-Bay Standalone Access Control Server with HDMI, DVI and Display port, Supports External Storage (eSATA, iSCSi), 1-Bay (Storage Disks not included), Audio, AC 100-240V |


Access Control System - Access Card

| | | |
|-----------|---|---|
| PACD-0001 |  | SAG RFID Card ISO/IEC 15693 13.56 MHz (20-pcs pack) |
|-----------|---|---|


Network & Storage Peripherals - Data Switch

| | | |
|-----------|---|---|
| PPSW-0100 |  | PLANET FGSD-910HP 8-Port 802.3at PoE Switch (PoE Budget 120W) |
| PPSW-0101 |  | PLANET GS-4210-8P2T2S 8-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 240W) |
| PPSW-0102 |  | PLANET FGSD-1011HP 8-Port 802.3at PoE Switch (PoE Budget 120W) |
| PPSW-2101 |  | 4-Port 802.3at PoE Switch (PoE Budget 62W) |
| PPSW-3100 |  | PLANET FGSW-1816HPS 16-Port 802.3at PoE Switch (PoE Budget 220W) |




Extenders - PoE Extender

| | | |
|-----------|---|--|
| PPEX-0100 |  | Veracity OUTREACH Max Power over Ethernet (PoE) Extender |
|-----------|---|--|

Extenders - PoE over Coaxial Extender Kit

| | | |
|-----------|---|---|
| PPOC-0100 |  | Planet LRP-101C-KIT Power over Coax Adapter Kit |
|-----------|---|---|

Installation Support - Camera Installation Kit

| | | |
|---------------|---|--|
| PMON-1001-010 |  | Camera Installation Kit for use with iOS Device with belt bag, battery and charger (US, AC 110~240V) |
| PMON-1001-011 |  | Camera Installation Kit for use with iOS Device with belt bag, battery and charger (Europe, AC 110~240V) |
| PMON-2000 |  | Camera Installation Kit |