# **DTK-1F Series**

## **Single Outlet Surge Protection**





DTK-1FF

**DITEK's DTK-1F Series** single outlet surge protectors provide robust surge protection at a reasonable cost. The unique center screw design that secures the surge protector and, if installed, a transformer, to the wall prevents accidental disconnections. Models are available to protect AC power and telephone lines.

#### **Product Features**

- Single AC outlet protects critical equipment
- Center screw secures to outlet and can also secure a connected transformer
- Diagnostic LED indicates AC power, ground presence and suppressor function
- AC protection 40,000A: DTK-1
- AC and Telco protection: DTK-1FF

#### **Applications**

- Alarm Panel Transformers
- Point of Use Appliances
- Answering Machines
- Fax Machines

Technical Specifications		
Part Number:	DTK-1F	DTK-1FF
Service Voltage:	110-120VAC	
MCOV:	127VAC (Power & Telco)	
Protection Modes:	L-G, L-N, N-G (AC) Tip-G, Ring-G, Tip-Ring (Telco)	
Voltage Protection Rating:	500V	
Surge Current Rating:	40,000A	30,000A
Max Continuous Current:	15A (AC)	125mA (Telco)

#### **Mechanical Characteristics**

Connection Method:	Direct plug-in(AC)	RJ11/14(1FF)
Housing:	ABS	
Operating Temperature:	0°C - 40°C (32°F - 104°F)	
Dimensions:	2.71"L x 1.25"W x 1.385"H (69mm x 32mm x 47mm)	
Weight:	0.25 lb (113g)	

### **Quality, Standards & Approval**

Agency Approvals:	UL1449
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

Doc. Number: SPS-100001-001 Rev 12 10/20



