



ELEV-C2DRIRA2812DN

2 Megapixel TVI/AHD/CVI Analog Outdoor Dome, 2.8-12mm Motorized Auto-Focus, up to 98' IR Range, D-WDR, Dual Voltage

Features

- 2 Megapixel Resolution
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Motorized Auto-Focus 2.8-12mm Lens
- True Day/Night with IR Range up to 98'
- Smart IRs
- D-WDR
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 2D/3D DNR (Digital Noise Reduction)
- DC12V/AC24V
- Joystick Support
- Through InVid Tech DVR: Free App, CMS & MAC Client

Camera	ELEV-C2DRIRA2812DN
Image Sensor	1/2.8" SONY CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	AUTO/ 1/50(1/60) -1/50,000sec
Min. Illumination	0.01Lux
Video Frame Rate	PAL/NTSC: 1080p@30fps
Video Output	*TVI / CVI / AHD : 2MP CVBS*
Video Output Default	TVI: 2MP
OSD Joystick	Support
UTC Control	Support
Camera Features	
S/N Ratio	>41dB
Noise Reduction	2D&3D DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Auto / Manual/Indoor/Outdoor
OSD Language	English / Chinese / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish / Korean / Japanese
AGC	Auto
Mirror Image	Yes
Sharpness	Yes
Defogging	Yes
BLC	Yes
DWDR	Yes
Smart IR	Yes
IR LED	30pcs IR LED
IR Range	98ft(30M)
Lens	
Focal Length	2.8-12mm Motorized Auto Focus Lens
Angle of View	Horizontal FOV: 40°-97° Vertical FOV: 23°-54°
Lens Type	Fixed Iris
Mount Type	Φ 14
General	
IP Rating	IP66, IK10
Power Supply	DC12V / AC24V
Power Consumption	<6W
Working Temperature / Humidity	-4°F~ 122°F (-20~+50°C) RH95% MAX
Dimensions(W×D×H)	φ5.56" x 4.33"
Weight	1.76 lbs (800g)

Ordering Information

ELEV-C2DRIRA2812DN: 2 Megapixel Dome, 2.8-12 A/F Motorized