



ELEVI-P8DRXIRA27135

8 Megapixel IP Plug & Play, Outdoor Bullet, 3.6-11mm Auto-Focus Motorized, 114' IR Range, WDR, Audio Input/Output, SD Card Slot, White Light Motion, PoE/DC12V

Features

- 8 Megapixel (3840 x 2160) Resolution
- Motorized Auto-Focus 3.6-11mm Lens
- H.265/H.265+/H.264/H.264+ Compression
- True Day/Night
- True WDR 120dB
- White Light Motion Sensor
- Smart IR Range up to 114'
- TF Card Local Storage, 128GB
- Audio Input/Output
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Elevate Model	ELEVI-P8DRXIRA27135
Sensor+DSP	IMX415+Hi3516AV200
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens	2.8-12 mm@F1.4: horizontal FOV: 102°~39°, vertical FOV:56°~22°
Lens Mount	14
IR	14milX30pcs SMD LED
IR Range	50m (165ft)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR&DWDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Triple Streams	Support
Audio Compression	G.711A, G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	8MP(3840 × 2160)(default 15fps)
Frame Rate	50Hz: 15fps 8MP(3840 × 2160), 25fps 5MP(2592 × 1944) 25fps 4MP(2560 × 1440), 25fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536), 25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz: 15fps 8MP(3840 × 2160), 30fps 5MP(2592 × 1944) 30fps 4MP(2560 × 1440), 30fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536), 30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)
Sub Stream	50Hz: 25fps 720P(1280 × 720) 25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz: 30fps 720P(1280 × 720) 30fps D1(704 × 480), 30fps CIF(352 × 240)
Image Setting	50Hz: 25fps CIF(352 × 288) 60Hz: 30fps CIF(352 × 240) Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour*
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing, Area Intrusion, Unattended Object, Object Missing, Region Entrance, Region Exiting, Fast Moving, Loitering Detection, People Gathering Detection, Parking Detection, Blurred Detection, Scene Change Detection, Audio exception Detection, Crossing Line Statistics, Human Body Detection
System compatibility	Onvif(Profile S), CGI
Security	User authentication, IP address filtering, Video mask
Mobile Surveillance	iPhone, iPad, Android CMS WEB
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
TF	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
MIC	Support
General	
Operating Conditions	-22°F~140°F (-30°C~60°C) Humidity 95% or less (non-condensing) *
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Vandalproof	IK10
Dimensions	6 x 5 in (142 x 113.4 mm)
Weight	2 lbs (940g)

Ordering Information

ELEVI-P8DRXIRA27135: 8 Megapixel A/F Bullet, 3.6-11mm